

METHOD AND APPARATUS FOR DETONATING AN EXPLOSIVE CHARGE

Background of the Invention

The Field of the Invention

The present invention relates to a method and apparatus for detonating an explosive
5 charge and, in particular, to wireless transmission down a well for accurate and controlled
perforating of a tubular by explosive charges.

The Prior Art

09396432-062901
10 Once a well bore has been drilled, utilizing the conventional technique of a drilling string
with a drill bit secured to the lower free end, the well is completed by positioning a casing string
within the well bore. This increases the integrity of the well bore and provides a path to the
surface for the produced fluids. The casing string is normally made up of individual lengths of
relatively large diameter metal tubulars secured together by any suitable means, for example screw
threads or welds. Conventionally, the casing string is cemented to the well face by circulating
cement into the annulus defined between the casing string and the well face. The cemented casing
15 string is subsequently perforated to establish fluid communication between the formations of
interest, those containing hydrocarbons, and the interior of the casing string. Perforating has
conventionally been performed by means of lowering a perforating gun, having at least one shaped
charge positioned within a carrier, down inside the casing string and then firing the charge via
wireline control from the surface of the earth. A perforating gun may be constructed to be of any
20 length. The perforating gun is lowered within the casing on wireline or tubing to a point adjacent

the zone of interest and the shaped explosive charge is detonated to penetrate or perforate both the casing and the formation. This establishes fluid communication between the cased well bore and the zone of interest. The resulting perforations extend through the casing, cement, and a short distance into the formation. The perforating gun is either removed from the well bore or
5 dropped to the bottom thereof. The formation is then often stimulated by any one of a number of well-known means to enhance production of hydrocarbons therefrom.

Examples of the known perforating devices can be found in U. S. Patent Nos. 4,538,680 to Brieger et al; 4,619,333 to George; 4,768,597 to Lavigne et al; 4,790,383 to Savage et al; 4,911,251 to George et al; 5,287,924 to Burleson et al; 5,423,382 to Barton et al; and 6,082,450 to Snider et al. All of these relate to perforating guns which are lowered within a casing string carrying explosive charges which are detonated to perforate the casing outwardly. This had the advantage of leaving the inside of the casing relatively unobstructed since debris and ragged edges would be outwardly directed by the detonations of the charges.

In the late 1990s, successes were found with casing conveyed perforating guns in which the guns and control lines were attached to the outside of the casing. One disadvantage of this approach is that the externally conveyed elements are subject to damage during normal run-in operations. A second disadvantage is the perforations leaving ragged shards extending inwardly causing obstructions on the inside of the casing.

PCT application PCT/US00/05774, to Snider et al, describes another attempt to perforate
20 a tubular from the outside. This differs from the above mentioned perforating from the outside of the casing in that Snider et al propose a perforating gun separate from and exterior to the casing to be perforated. When the Snider et al perforating gun is detonated, portions of the gun act in a

manner similar to shrapnel to perforate the casing string. This is not a satisfactory solution to the problem of perforating tubulars in that it raises the possibility of a very ragged perforating which could easily destroy the structural integrity of the casing string, particularly in view of the fact that it utilizes portions of the casing itself to perforate the side of the casing furthest from the perforating gun. This can also result in a ragged inner surface of the casing which could damage or prevent passage of downhole tools and instruments. Perforating a casing from the inside raised this consideration to a much lesser degree.

Frequently a well penetrates multiple zones of the same formation and/or a plurality of hydrocarbon bearing formations of interest. It is usually desirable to establish communication with each zone and/or formation of interest for injection and/or production of fluids. Conventionally, this has been accomplished in any one of several ways. One way is to use a single perforating gun which is conveyed by wireline or tubing into the well bore and an explosive charge fired to perforate a zone and/or formation of interest. This procedure is then repeated for each zone to be treated and requires running a new perforating gun into the well for each zone and/or formation of interest. One alternative is to have a single perforating gun carrying multiple explosive charges. This multiple explosive charge gun is conveyed on wireline or tubing into the well and, as the gun is positioned adjacent to each zone and/or formation of interest, selected explosive charges are fired to perforate the adjacent zone and/or formation. In another alternative, two or more perforating guns, each having at least one explosive charge, are mounted spaced apart on a single tubing, then conveyed into the well, and each gun is selectively fired when positioned opposite a zone and/or formation of interest. When the select firing method is used, and the zone and/or formation of interest are relatively thin, e.g., 15 feet or less, the

perforating gun is positioned adjacent the zone of interest and only some of the shaped charges carried by the perforating gun are fired to perforate only this zone or formation. The gun is then repositioned, by means of the tubing, to another zone or formation and other shaped charges are fired to perforate this zone or formation. This procedure is repeated until all zones and/or formations are perforated, or all of the shaped explosive charges detonated, and the perforating gun is retrieved to the surface by means of the tubing.

However, the necessity of tripping in and out of the well bore to perforate and stimulate each of multiple zones and/or formations is time consuming and expensive. In view of this, multiple zones and/or formations are often simultaneously stimulated, even though this may result in certain zones and/or formations being treated in a manner more suitable for an adjacent zone and/or formation. Thus a need exists for apparatus and processes to perforate casing which is positioned within a well bore which eliminates the need to run perforating equipment in and out of the well when completing multiple zones and/or formations.

Disadvantages of the presently known methods of perforating are several, including: the perforating device itself may need to be retrieved; and the cabling systems to convey signals to the charges must be carried outside or inside the tubulars, either subjecting the cabling system to damage and/or taking up space. Protective means, such as wraparound metal protectors, armored cable housings, or grooved casing couplings, must be used to avoid damaging externally mounted cabling systems, explosive charges and their respective detonating means. In order to perforate the adjacent formation, internally conveyed or mounted perforating systems necessarily also perforate the tubular within which they are conveyed which in certain instances, such as when trying to relieve annular pressure, is undesirable.

Accordingly, it is an object of the present invention to provide a method and apparatus for economically and effectively detonating an explosive charge.

It is another object of the present invention to provide a process and apparatus for completing a well wherein the casing is perforated from the outside with the explosive charges being detonated in response to a wireless and cableless signal from a control station at the earth's surface.

It is a further object of the present invention to provide a method and apparatus for perforating tubulars wherein shaped explosive charges are mounted in contact with, or at least partially embedded in, the external casing wall so that a precise hole is formed without undue damage to the casing or unwanted internally directed projections left to interfere with passage of tools and/or instrumentation through the casing.

It is still another object of the present invention to effect detonation of explosive charges utilizing wireless communication from the surface to initiate detonation of respective explosive charges, the wireless communication employing coded signaling to prevent errors in detonation.

Summary of the Invention

The present invention provides a method and apparatus for detonating explosive charges wherein at least one explosive charge is in contact with the outside surface of a wall with at least one detonation device in communication with the at least one explosive device. The detonation device includes a programmable logic interface to arm and fire the detonation device in response to receipt of a coded signal from a control station in wireless and cableless communication with the programmable logic interface.

The present invention also provides a method for detonating an explosive device

comprising the steps of providing at least one explosive charge in contact with the outside surface of a wall and providing a detonation device in communication with each explosive charge. Each detonation device includes a programmable logic interface to arm and fire the detonation device in response to receipt of a coded signal from a control station in wireless and cableless communication with the programmable logic interface to effect the detonation.

Brief Description of the Drawings

The present invention will now be described, by way of example, with reference to the accompanying drawings in which:

Figure 1 is a side elevation, partially in section, of an embodiment of the invention utilizing explosive charges attached to a tubing wall;

Figure 2 is a detailed section through one of the shaped charges of the present invention;

Figure 3 is a side elevation of an embodiment of the invention utilizing external ribs containing the explosive charges;

Figure 4 is a side elevation of an embodiment of the invention utilizing an explosive linear strip;

Figure 5 is a block level schematic diagram of the programmable interface and detonation device; and

Figure 6 is a detail plan view of the exploding bridgewire detonation device of the present invention.

Detailed Description of the Invention

The method and apparatus of the present invention is described in an embodiment for perforating a tubing string and the adjacent formation without the need for conventional

01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 10

20

Such sleeves could be made to attach to the outside surface of the tubular, for example in a clamping manner or as shrink wrap, and could be provided with additional features, such as molded channels to allow circulation of well fluids, for example cement slurry, through the annular space between the casing and the well bore.

INS.
A2

Figure 2 shows a cross section through an explosive charge 18 in accordance with the first embodiment. The tubular 10 is first prepared by boring a series of blind bores 20 about the circumference. These bores 20 can be in set geometric patterns, randomly spaced, aligned vertical rows, circumferential bands, etc. in accordance with the desired plan for perforating. The shaped explosive charges 18 are secured in their respective blind bores 20 by any known means, such as threading or affixing the explosive charge into the blind bore with an adhesive material. The explosive charges 18 are then connected to their respective detonating means (not shown) for single, multiple, sequential, etc. detonation in accordance with the plan for perforating. The detonating means are in wireless/cableless contact with control means (also not shown) at the surface. When the explosive charge 18 is detonated, it will shear a plug 22 (shown in phantom) from wall 14. This amounts to no-jet perforating.

This preferred method to perforate the pipe string uses an explosive charge to open a hole from outside to inside to create a flow path between the inside and outside of the pipe. A second explosive charge can, if so desired, be used to perforate outwardly through the annular space, which may be cement filled, into the formation or zone of interest. The present method can be considered "plugging" in that an explosive charge is set in contact with the casing wall, or in a partially penetrating blind bore drilled into the casing wall, and detonation of that explosive charge creates a stress riser that shears a steel "plug" out of the casing wall leave a hole of known

geometry and size without burrs or splatter inside the casing that can block or damage equipment being run in the hole.

A key feature of the present system is the slim overall profile which does not increase borehole size requirements.

5 A collar, sleeve or coating of a diameter greater than that of the casing and with channel(s) cut helically on its exterior surface can be used to provide protected clearance for the charge, receiver, and controller while allowing clearance for flow of fluids and slurries, for example cement, past the collar. A hole or holes can be partially drilled into the collar from the outside to provide a site for a stress riser when the perforating charge is ignited without substantially affecting the pressure rating of the casing string.

In Figure 3, a tubular 24 has an outside surface 26 and one or more ribs 28 wrapped around and secured to the outside surface. A plurality of explosive charges 30 are placed in recesses in the ribs 28 to lie against the outer surface 26. This embodiment maintains full strength of the tubular, as the wall is without the blind bores of the embodiment of Figure 1, but has a slightly larger profile. However, the ribs 28 can be used to advantage by directing flow during casing running and cementing operations.

20 The embodiment of Figure 4 utilizes a linear strip or shaped explosive charge 32 placed on and winding helically about the outside surface 34 of the tubular 36 oriented to shoot outward into the cement and/or formation. Such helically arranged linear strip charges provides a channel for flow and exposes a greater surface area of rock/sand to be perforated, as compared to conventional "button" or conical shaped charges. The flexible strips may be oriented in a variety of patterns. Explosive strips may be constructed so that the force of the explosion is highly

directional. When explosive linear strips are used, it is advisable to place them on the outside surface of the outermost tubing string, such as the casing, so that the force is directed outward and the structural integrity of the casing is not compromised. This is an important new advantage of the subject system.

5 With all of the above-mentioned embodiments of the present invention, the use of shaped explosive charges allows a controlled and directed explosive force thereby allowing use as a means to open holes to release annular pressure without damaging internal tubulars.

INS
A2
40396432-062301
5
Figure 5 shows a schematic of the detonation device of the present invention including a wireless receiver 38; digital signal processing logic and control 40; exploding bridge wire 42; high voltage supply 44; and energy storage and trigger means 46. A coded wireless signal from the control at the surface will be received by receiver 38, the digital signal processed by the associated micro processor based logic 40 and, if the code designates that the respective explosive charge is to be detonated, sends a signal to the trigger means 46 which will supply high voltage to explosive bridge wire 42 to trigger detonation of the respective explosive charge.

Among the advantages of this system are: the coded signal allows selective detonation of the explosive charges individually, in sequence, in patterns, etc., and the wireless signal does not transmit the power to initiate detonation of the explosive charge thereby reducing the risk of accidental detonation of the explosive charge.

20 Figure 6 shows a detail of an explosive bridge wire 42, which can be compared to a printed circuit board 48 with the bridge portion 50 of the circuit 52 overlying an aperture 54, thus bridge. The bridge 50 has dimensions smaller than the rest of the circuit 52, so that, upon application of power to the circuit 52, the bridge 50 will flash vaporize creating enough energy

to cause detonation of the nearby explosive charge 18.

The explosive charge is in communication with a detonation device which receives signals, via a programmable logic interface, to detonate the explosive charge. The explosive charges may be programmed and/or wired to fire independently of each other, or several may be linked together, in parallel or in series, to fire together. One explosive charge or several explosive charges may be connected to a single detonator. The detonator is typically conveyed into the well as an attachment to the casing/tubing, but it may be remote, such as at the surface.

The present invention has one or more antenna (not shown) embedded in the well casing to facilitate wireless communication with the surface. Embedding antennas into the casing and adding instrumentation to the casing allows all wells thus equipped to have increased capabilities for monitoring and/or further processing. Embedding antennas into the casing avoids irregular inside surface topography and its related problems. This allows normal inside casing well operations to be performed in an unhindered fashion. The embedded antenna resides in a relief area machined into the inside of each connection. It is generally circular in shape, but could have substantially any shape or form including, but not limited to, a single wire, a loop of wire, or a coil of looped wire. The antenna forms an electrically isolated area from the casing itself. The antenna can be designed to work with any frequency or communication protocol specified by the user. Many communication protocols and practical techniques exist for wireless communication through an empty or partially filled wave guide. The well bore casing would be such a wave guide. The antenna can be designed to work within any size of well casing. The antenna design, coupled with a properly designed transceiver unit, would allow more than one antenna to be embedded into the well casing, if so desired.

and attachment techniques with etched or plated circuit board traces. The exploding bridgewire trace is in contact with a small mass of low density explosive consisting of PETN, RDX, HMX or other secondary explosive to begin the detonation process. This small mass of low density explosive is in contact with a larger mass of high density explosive to complete the initiation process.

As a high voltage pulse is passed through the exploding bridgewire trace, the trace is vaporized and sends a shock wave into the low density explosive, initiating detonation. The low density explosive in turn initiates the larger mass of high density explosive to complete the detonation train. The output from this secondary charge can then be used to initiate larger masses of explosives. Additionally, the initial mass of low density explosive may be in contact with the final mass of high density explosive to be used in an explosive device.

The circuit board trace for the exploding bridgewire is shown in Figure 6. In the figure a wider trace that acts as a conductive path narrows down to the trace shown, the narrow trace acts as the exploding bridgewire. Variations in lengths, widths and thicknesses of the trace provide for tailoring of voltage and energy requirements for initiating the explosive. Variations of the trace sizes, types of explosives in contact with the traces, and densities of explosives are all considered to be pertinent to the method described.

The subject explosive bridge wire detonating system is a major improvement over the previously widely used primacord for detonation. The board can be built to withstand high operating temperatures, where primacord cannot be used because of its instability. The subject explosive bridge wire detonating system also provides a way to make selective perforating with conventional guns much cheaper and easier to operate. The digitally operated controller and

downhole battery power source provide easy selectivity for the system which enables the perforator to be constructed safely offsite and run in the hole without having to wait for a complete well evaluation, improving safety and saving rig time. In completion intervals that may be impacted by gas and water contact within a producing interval, the selectivity allows the system to be run into and cemented in the well before log evaluation is completed because the spacing of the charges would preferably overlap beyond the potential completion intervals.

The linear perforating charge increases the amount of formation exposed for completion. The linear charge is an outwardly directed jet perforator that is designed to penetrate the formation with a high velocity jet, not by expansion of gas. Also, the linear explosive charge can be used in combination with the above discussed "plugging" explosive charges and can be fired sequentially, e.g., first plugging holes in the casing and then firing the linear charge.

The coded wireless signal sent downhole in the present invention is used only to arm the explosive charges. The power to initiate the explosive charge comes from a battery positioned downhole as a part of the detonating system.

The present apparatus requires a control station and a wireless and cableless means for communicating between the control station and the detonation device. Any wireless or cableless communication method may be used including, but not restricted to, radio waves, infrared waves, acoustic waves, optical light waves, seismic waves, magnetic waves, or combinations thereof. Wireless signals are conveyed using the tubular string wall as a waveguide. Alternatively, a ball containing a transponder may be dropped downhole, sending signals to the controllers for the detonators as it passes them. If a "smart ball" or transponder is used, signals may vary as the smart ball progresses thus allowing only selected explosive charges to detonate.

